



V210 Video Phone

Android & Video conference terminal

The V210 is a premium video telephone with high end configuration to support high definition video and audio call. Besides the sleek and exquisite design, the V210 is equipped with a 5MP high definition camera, a 10 inch multi touch IPS screen and two HDMI ports to support sub stream for video conference. Configured with OCTA core, 2G RAM plus 16G Flash and running on Android 7.1 OS, the V210 supports heavy load software. With specific application software, the V210 can be used in hotels, hospitals, smart home control, intercom system etc.



Video conference terminal

With good video performance, V210 is compatible with video conferencing system by today's mainstream vendors. The two HDMI ports further extend users' video experiences for projection on TV and computer sharing. Screen recording function is available to record all the operations too.



Specific Application


CPL offers SDK for the video phone to integrate with various kinds of third-party software for business customization. With remote management system, users can easily manage their software update and installation



Note: we will soon launch the remote management system



Hardware details



Features



Android 7.1, Qualcomm 8953
OCTA Core, 2G RAM + 16G Flash

API

API/SDK for integrate third-party application



Two HDMI ports, HDMI-in and HDMI-out
Support main stream and sub stream
Wireless Screen sharing 1080p@30

SIP

SIP 2.0 Protocol, support SIP voice and video
4 SIP accounts



IPS multi touch screen
10.1 inch screen, 1280x800



5MP rotatable camera
Hard switch



2.4G/5.8G dual WIFI
IEEE802.11 b/g/n/ac



BT2.1+EDR/3.0/4.1LE
USB2.0, support U disk, keyboard, mouse etc.



Specification



| Items | | V210 Video Phone |
|--------------------------|---------------------|---|
| System Configuration | Operating System | Android 7.1 |
| | CPU | OCTA core |
| | FLASH | 16GB, eMMC |
| | RAM | 2GB, DDR3 |
| Screen Size | | 10.1", 1280x800, IPS multi touch screen |
| Camera | | 5 mega-pixel, angle adjustable |
| Display Angle Adjustment | | Display angle adjustable from 10 degree~70 degree |
| Ethernet Port | | 2 Ethernet ports, 10M/100M/1000M, adaptive; POE |
| HDMI | | Two HDMI ports, support HDMI-in and HDMI-out, can support sharing screen and input video auxiliary stream at the same time |
| Wireless Screen Sharing | | 1080p@30 |
| WLAN | | 2.4G/5.8G Dual Wifi, IEEE802.11b/g/n/ac, support AP and WLAN features |
| Bluetooth | | BT2.1+EDR/3.0/4.1LE |
| Storage Card | | 1 MicroSD (TF) |
| USB Port | | 1 USB2.0, support U disk, headphone, keyboard, mouse |
| Handset Port | | RJ-9 |
| Headphone Port | | one 3.5mm/Bluetooth headphone/USB headphone |
| Protocol | Network Protocol | SIP, TCP/IP, SIP, SDP, UDP, RTP, RTCP, DHCP, DNS, HTTP, HTTPS, SNTP, XCAP, IPv4, IPv6 |
| Audio | Audio Protocol | G.711a/G.711u/G.729/G.722/iLBC/SILK/OPUS/ACC/AMR-WB |
| | Audio Codec | DTMF: inband/RFC2833 AEC: Acoustic Echo Chancellor PLC: Packet Loss Concealment AGC: Automatic Gain Control VAD: Voice Activity Detection CNG: Comfort noise generator AJB: Adaptive Jitter Buffer Sidetone Cancellation ANR: Adaptive Noise Reduction VQM: Voice Quality Manager |
| | Voice Record | Support |
| Video | Video Codec | Encoding: H.264, VP8 Decoding: H.264, VP8, H265, MPEG-4 |
| | Video Resolution | QVGA (320 x 240) 、 CIF (352x288) 、 VGA (640x480) 、 4CIF (704x576) 、 720p (1280x720) 、 1080p(1920 x 1080) |
| | Video Display | Full screen show in opposite end, preview in local side with both showing and preview screen. |
| | Video Conference | Support China Mobile Cloud Video Conference Platform Support local/UC portal to launch conference Video output of main stream and auxiliary stream (1080P@30 Dual Streams) Video input of main stream and auxiliary stream (1080P@30 Dual Streams) Support same display in two screens, support different displays in two screens Conference operating in local side |
| Telephony | Contacts | 2000 contacts, support contacts search, import, export |
| | Call Logs | 1000 call logs for received calls, 1000 call logs for missed calls, 1000 call logs for dialed numbers |
| | Local Conference | 6 parties audio conference |
| | Telephony Features | Call Hold, Call Forward, Call Transfer, Three-Way Calling, Call Waiting, Call Reject, Call ID, Missed Call Reminder, Speed Dial |
| | Line & SIP Account | 4 lines, 4 accounts |
| | Android OS Features | Build-in APP: clock, gallery, web browser, search |
| Security | | TLS, SRTP(AES128) |
| Management | | WEB/TR069 |
| Customized Applications | | SDK/API for customer application development; Build-in company contacts |
| Power Adapter | | Input: AC100~220V Output: DC12V/1.5A |
| Size | | 300mm*200mm*72mm |